

### Cell Parameters

No.	Items	Parameters
1	Cell type	Prismatic
2	Nominal voltage	3.2V
3	Rated capacity	100AH
4	Rated energy	320WH
5	Internal resistance	≤0.4mΩ@25°C1kHz AC
6	Allowed MAX charging current	1C
7	Recommended charging current	≤0.5C
8	Allowed MAX discharging current	1C @25±5°C, SOC > 20%
9	Maximum pulse discharging current	2C@25±5°C, 10s, SOC≥20%

### Battery Module Parameters

No.	Items	Parameters
1	Product name	LiFePO4 Battery System
2	Rating	51.2V, 100Ah, 5.12Kwh
3	Depth of Discharge	90%
4	Useable Capacity	100 Ah
5	Input	Max 56.8V d.c., 60A
6	Output	43.2 ~ 56.8V d.c., Max 60A
7	Charging Temperature Range	0°C ~ 45°C
8	Discharging Temperature Range	-10°C ~ 55°C
9	Internal resistance	≤20mΩ @1kHz AC
10	Rated charge voltage	58.4V
11	Short Circuit Protection	500A
12	Short Circuit Protection Delay Time	200 - 800 us
13	Communication Port Type	CAN
14	Communication Protocol	RS485
15	Wi-Fi / LAN connection capability	No comply
16	Allowed MAX charging current	60A @ 25±5°C
17	Recommended charging current	≤50A
18	Allowed MAX discharging current	60A @ 25±5°C
19	Dimensions	W:400±2mm D:620±2mm H:145±2mm
20	Weight	About:56kg
21	IP Class	IP55



Members of:



Redx Technology Australia Pty Ltd

Unit 2/21 Millennium Circuit

HELENSVALE QLD 4212

+61 (0) 7 5672 9983

sales@redx.com.au

www.redx.com.au

# Redx

Country of manufacture: China