

Safety Data Sheets (SDSs)

Product Name: Battery Energy Storage System

Commissioner: Redx Technology Australia Pty Ltd

Safety Data Sheets (SDSs)

Ref, No.: RZUN2023-4334-DS1

Page 2 of 9 Pages

Name of Product	Battery Energy Storage System
Type/Model	RX-5006Plus/7006Plus RX-5010Plus/7010Plus RX-5013Plus/7013Plus
Commissioned by	Redx Technology Australia Pty Ltd
Commissioner address	Unit 2/21 Millennium Circuit, Helensvale, QLD 4212, AUSTRALIA
Supplier	Redx Technology Australia Pty Ltd
Supplier address	Unit 2/21 Millennium Circuit, Helensvale, QLD 4212, AUSTRALIA
Factory	Guangdong Redx Electrical Technology Ltd.
Factory address	Room 601-609, 6th Floor, Building 1, No.19, 4th Ke Ji Road, Songshan Lake Park, Dongguan, Guangdong, China
Inspection according to	GLOBALY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS, Rev.9)
Emergency telephone number	+61 7 5672 9983
Remarks	
Seal of CVC	
Date of issue 2024-01-23	

Approved by: Huang Kun

Huang Kun

Reviewed by: Zhang Siyao

Zhang Siyao

Tested by:

Lin Qingyuan

Lin Qingyuan

Safety Data Sheets (SDSs)

Ref, No.: RZUN2023-4334-DS1

Page 3 of 9 Pages

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Identifier :

Product name: Battery Energy Storage System

Model: RX-5006Plus/7006Plus RX-5010Plus/7010Plus RX-5013Plus/7013Plus

Other means of identification :

Synonyms: None

Relevant identified use of Product and uses advised against :

Recommended Use: Applied to electronic products

Uses advised against: Don't disassemble, impact, crush, put into fire or water, don't use above 60 °C !

Details of the Supplier of the safety data sheet :

Name: Redx Technology Australia Pty Ltd .

Address: Unit 2/21 Millennium Circuit, Helensvale, QLD 4212, AUSTRALIA

Telephone: +61 7 5672 9983

Fax: -

Postcode: -

E-mail address: Adam.wang@redx.com.au

Emergency telephone number :

Company Emergency Phone Number: +61 7 5672 9983

SECTION 2: HAZARDS IDENTIFICATION

Classification :

The watt-hour rate of the product is 3.34kWh, it is belong to the class 9 dangerous goods.

The product is tested according to Section 38.3 of the Manual of Tests and Criteria, the test report number is: RZUN2023-4334

Other information

Caution! Avoid short circuit place in high temperature environment, put into water, or damage the shell.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description: Chemical power supply based on nonaqueous electrolyte. Composed by positive electrode, negative electrode, diaphragm, electrolyte and shell.

Hazardous ingredients:

Safety Data Sheets (SDSs)

Ref. No.: RZUN2023-4334-DS1

Page 4 of 9 Pages

Common Chemical Name	Chemical Formula	Concentration (%)	CAS No.	EC No.
Lithium iron Phosphate	LiFePO ₄	15-40	15365-14-7	604-917-2
Ethyl propionate	C ₅ H ₁₀ O ₂	15-40	105-37-3	23-291-4
Copper foil	Cu	7440-50-8	10-30	231-159-6
Aluminum foil	Al	7429-90-5	10-30	231-072-3
Graphite	C	7782-42-5	7-25	231-955-3
Hexafluoropropylene-vinylidene fluoride Copolymer	C ₂ H ₂₂ C ₁₉ N ₃ O ₂	3-15	9011-17-0	618-470-6
Ethylene Carbonate	C ₃ H ₄ O ₃	0-15	96-49-1	202-510-0
Propylene Carbonate	C ₄ H ₆ O ₃	0-15	108-32-7	203-572-1
Lithium Hexafluorophosphate	F ₆ LiP	0-15	21324-40-3	244-334-7
Separator	/	0-5	/	/

Note: N/A=Not apply.

SECTION 4: FIRST-AID MEASURES

First aid measures:

Eye Contact: Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Skin Contact: Remove contaminated clothing and shoes. Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician.

Swallowing: Do not induce vomiting. Get medical attention.

Most Important Symptoms/Effects:

No information available.

Indication of any immediate medical attention and special treatment needed:

Inform physician. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

CO₂, dry chemical powder, wet sand, plenty of water (for cooling).

Unsuitable Extinguishing Media: No information available.

Safety Data Sheets (SDSs)

Ref, No.: RZUN2023-4334-DS1

Page 5 of 9 Pages

Protective Equipment and Precautions for Firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. For example: Wear self-contained respiratory protective device. Wear suitable protective clothing and eye/face protection.

Special hazards arising from the substance or mixture:

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium batteries contain flammable ingredients that may vent, ignite and produce sparks when subjected to high temperature (>150°C), When damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in close proximity.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions Avoid contact with eyes.

Refer to section 8 for personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Environmental precautions:

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Methods and material for containment and cleaning up:

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning up Use personal protective equipment. Dam up. Cover liquid spill with sand, earth or other Non-combustible absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:

Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Avoid mechanical or electrical abuse.

More than a momentary short circuit will generally reduce the battery service life. Avoid reversing battery polarity within the battery assembly. In case of a battery unintentionally be crushed, rubber gloves must be used to handle all battery components. Avoid contact with eyes, skin. Avoid inhalation. No smoking at working site. Materials to Avoid: Strong oxidizing agents, Corrosives.

Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated area. Keep away from ignition sources, heat and flame. Such batteries must be packed in inner packages in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short-circuits. Materials to Avoid: Strong

Safety Data Sheets (SDSs)

Ref. No.: RZUN2023-4334-DS1
oxidizing agents, Corrosives.

Page 6 of 9 Pages

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls:

Use ventilation equipment if available. Safety shower and eye bath.

Personal Protective Equipment:

Respiratory System: Not necessary under conditions of normal use.

Eyes: Not necessary under conditions of normal use.

Clothing: Wear appropriate protective clothing. ,

Hand: Safety gloves.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION 9: Physical and chemical properties

PhysicalState	Form: Prismatic
	Color: White
	Odour: Odourless
	Odor Threshold: No information available
Change in condition:	
pH, with indication of the concentration	Not determined.
Melting point/freezing point	Not determined.
Initial boiling point and Boiling range:	Not determined.
Flash Point	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Auto-ignition temperature	Product is not self-igniting.
Decomposition temperature	Not determined.
Other Information	No further relevant information available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Stable under recommended storage and handling conditions (see section 7).

Chemical stability: Stable under normal conditions of use, storage and transport.

Safety Data Sheets (SDSs)

Ref, No.: RZUN2023-4334-DS1

Page 7 of 9 Pages

Thermal decomposition/conditions to be avoided: No decomposition if used according to specifications.

Possibility of Hazardous Reactions: None under normal processing.

Hazardous Polymerization: Hazardous polymerization does not occur.

Conditions to avoid: Strong heating, fire, Incompatible materials.

Incompatible materials: Strong oxidizing agents. Strong acids.

Hazardous Decomposition Products: Carbon oxides, other irritating and toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity: No data available.

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Cause serious eye irritation.

Respiratory or skin sensitization: No sensitizing effects known.

Specific target organ system toxicity: No information available.

Note: The internal battery materials may cause irritation to eyes and skin.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods:

Recommendation: Lithium batteries are best disposed of as a non-hazardous waste when fully or mostly discharged. Contact a licensed professional waste disposal service to dispose of large quantities materials.

Other disposal recommendations:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: TRANSPORT INFORMATION

The product had been tested according to the requirements of the UN manual of tests and Criteria,

Safety Data Sheets (SDSs)

Ref. No.: RZUN2023-4334-DS1
Part III, subsection 38.3 (see section 2)

Page 8 of 9 Pages

EmS No: F-A, S-I

Marine pollutant: No

Environmental hazards: Not applicable.

Special precautions for user: Not applicable.

Proper Shipping name: Lithium ion batteries (Including lithium ion polymer batteries)

Hazard Class: Class 9

UN/ID Number: UN3480

Packaging Group: II

Air transport:

Label for conveyance: Class 9 lithium battery hazard label, Cargo Aircraft Only Label

The goods are complied with the requirements of Section IA of Packing Instruction 965 of 65th DGR Manual of IATA (2024 Edition).

Maritime transport:

Label for conveyance: Class 9 lithium battery hazard label

The goods are complied with the requirements of Packing Instruction P903 of IMDG CODE (Amdt. 41-22) (2022 Edition)

Land transport:

Label for conveyance: Class 9 lithium battery hazard label

The goods are complied with the requirements of Packing Instruction P903 of Agreement concerning the International Carriage of Dangerous Goods by Road (ADR 2023)

SECTION 15: REGULATORY INFORMATION

International Regulation:

 GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS)

 Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations
 IATA Dangerous Goods Regulations (DGR)

 INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG CODE)

EU Regulation:

 EU regulation (EC) 1272/2008 on "Classification, Labeling and Packaging of Substances and Mixtures" (CLP)

 Registration, Evaluation and Authorization of Chemicals (REACH)

 Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)

US Regulation:

 American National Standard for Hazardous Workplace Chemicals – Hazard Evaluation and Safety Data Sheet and Precautionary Labeling Preparation

 US DOT, Code of Federal Regulations, Title 49, Transportation, PT. 100-185

SECTION 16: OTHER INFORMATION

Safety Data Sheets (SDSs)

Ref, No.: RZUN2023-4334-DS1

Page 9 of 9 Pages

This file is only effective to the Battery Energy Storage System (RX-5006Plus/7006Plus RX-5010Plus/7010Plus RX-5013Plus/7013Plus) provided by commissioner Redx Technology Australia Pty Ltd. The commissioner provides the composition information of Battery Energy Storage System and promises its integrity and accuracy. Users should read this file carefully, and use the Battery Energy Storage System in correct method.
